

High Purity TXP

Laboratory Certified Steel Ball Tip Paint Marker

FEATURES

- Ideal for marking on any surface where degradation, contamination or other adverse effects are a concern.
- Paints are certified by an outside laboratory, refer to our website at <http://itwprofessionalbrands.com> for copies of the various certifications.
- Paints contain trace amounts of halogens, low melting point elements and chlorides.
- Paints meet or exceed the requirements of the US Energy Research & Development Administrations Nuclear Grade for Black, Yellow and White.
- Writes through oil and grease without losing legibility or brightness.
- Mark in extreme conditions, even writes under water and on rusty surfaces.
- Ergonomically correct marker that enables you to mark at all angles, even upside down.
- Markers can be used to permanently identify inventory, assemblies, tools, finished products or work in progress while resisting most work related abuses or compounds.
- Heavy duty aluminum body with large paint capacity.
- Paint flow is controlled by the pressure bulb at the end of the barrel.
- Stainless steel ball tips won't wear out on rough or rusty surfaces.
- Available in medium tip size. .

MATERIALS COMPATIBILITY

- Safe on most surfaces.
- Surface tests should be run to determine compatibility prior to use.

AVAILABLE IN:

<u>Color</u>	<u>Fine</u>	<u>Medium</u>
White	NA	17463

HEALTH AND SAFETY

- Combustible liquid and vapor. Keep away from heat, sparks and flame. Use only with adequate ventilation. Avoid contact with skin and eyes.
- Refer to SDS (Safety Data Sheet) for complete information on health and safety. Visit our website to obtain SDS.

DIRECTIONS FOR USE

- To start flow press rubber bulb to pressurize
- Depress steel ball tip to start flow.
- Wipe tip clean before storing

PHYSICAL PROPERTIES

Appearance:	Varies
Odor:	Mild
Specific gravity:	>1
VOC level:	29% - 42% by weight
Flash point:	105°F
Dry Time*:	25-35 minutes

* Note: Drying time may vary depending on film thickness.