



## Technical Data Sheet

# CRAMOLIN® CONTACTLEAN Art. No.101

### Product description

CONTACTLEAN cleans contacts of all types and efficiently removes oxide and sulphide layers from any metallic contact surfaces. Simultaneously, special inhibitors ensure long lasting lubrication and corrosion protection. It reduces the contact resistance that leads to failures down to values below 2 m $\Omega$  and eliminates voltage drops. CONTACTLEAN guarantees a durable preservation of the perfect operational reliability of all electromechanical contacts.

### Application

CONTACTLEAN can be used on switches of all types and on sliding contacts of variable capacitors, contact banks and relays. Further for the cleaning and maintenance of metallic surfaces in electrical engineering. CONTACTLEAN is used in the measurement technique, telecommunications, data processing, aerospace and military. Particularly suitable for electronic and electric motorcar equipment, too.

### Please note

Electronical devices to be switched-off during cleaning and plug to be taken out.  
Cleaning instructions of appliance producer to be taken into account.  
Further information concerning CONTACTLEAN to be found in recent MSDS.



### Technical Data

Appearance:	reddish liquid
Odor:	characteristic
Density at 25° C:	0,73 [g/cm <sup>3</sup> ]
Reduction of the contact resistance:	< 2[m $\Omega$ ]
Residue:	oily film
Material compatibility:	good
Temperature resistance:	up to + 80 [° C]

### Storage / Shelf Life

Shelf life is 2 years if stored correctly.  
Package after emptying to be disposed via metal scrap.