



Technical Data Sheet

CRAMOLIN® SPRAYOIL Art. No. 111

Product description

SPRAYOIL is a powerful, very fluid, absolutely acid-free lubricant that shows excellent emergency running properties. Its lubricating film is persistent and does not become gummy.

Further it repels water and moisture, thus ensuring durable and reliable corrosion protection.

SPRAYOIL remains effective over a wide temperature range from -40° C up to + 170° C and meets the requirements of standard ISO VG 10.

Application

SPRAYOIL is suitable for the lubrication of all types of moving parts in electrical and mechanical engineering, precision engineering, maintenance and repair work. Furthermore for the corrosion protection of components, appliances, automatic lathes, machines etc. SPRAYOIL can be used on all types of metals, plastics and rubber.

Please note

Insert the extension tube into the spray button and apply a thin film on the surface. The high penetrating capability of SPRAYOIL enables it to reach places of difficult access. Repeat the procedure from time to time to ensure perfect lubrication and corrosion protection.

Electronical devices to be switched-off during cleaning and plug to be taken out. Cleaning instructions of appliance producer to be taken into account. Further information concerning SPRAYOIL to be found in recent MSDS.



Technical Data

Appearance:	clear, yellowish liquid
Odor:	mild
Density aerosol at 20°C:	0,78[g/cm ³]
Viscosity film at 40°C:	10[mm ² /s]
Compability with materials:	good
Temperature resistance:	-40 to +170 [° C]
Evaporation rate:	middle

Storage / Shelf Life

Shelf life is 2 years if stored correctly.
Package after emptying to be disposed via metal scrap.