



Technical Data Sheet

CRAMOLIN® FLUX-OFF Art. No.107

Product description

FLUX-OFF is a mild, but effective cleaner, that readily removes the toughest deposits of organic flux, soldering oils, and other contaminants such as grease dirt and molding compounds from printed circuit boards and all other components. FLUX-OFF is colorless and leaves no deposits. It does not attack any material in common use. However, avoid using it on PVC and polystyrene.

Application

FLUX-OFF is especially suitable for a gentle, but intensive cleaning of printed circuit boards, electronic sub-assemblies and all other electronic components. Further it is also suitable for the degreasing of installations and appliances.

Spray FLUX-OFF thoroughly on residues to be removed. For accurate work, use the attached extension tube. Allow the solvents to act for a time. To protect printed circuit boards after the cleaning process, we recommend the use of PLASTIK, URETHANE CLEAR or ISOTEMP. FLUX-OFF is also available with a brush for difficult to clean areas.

Please note

Electronical devices to be switched-off during cleaning and plug to be taken out. Cleaning instructions of appliance producer to be taken into account.

Further information concerning FLUX-OFF to be found in recent MSDS.



Technical Data

Appearance:	clear, colorless liquid
Odor:	characteristic, mild
Density at 25° C:	0,84 [g/cm ³]
Material compatibility:	good
Evaporation:	average
Plastic compatibility:	PE, PP good PC limited PS, PVC incompatible
Surface tension:	22 [mN/m]

Storage / Shelf Life

Shelf life is 2 years if stored correctly.
Package after emptying to be disposed via metal scrap.